

### VALEN 24V6A

The Valen 24V 6A Convection Cooled Charger boasts superior quality and reliability with the ability to correctly charge and maintain mobility batteries ensuring longevity. This has an input voltage of 110V to 240V allowing it to operate universally. Thermal protection against overheating is also built in as well as reverse polarity, output shorting and spark protection.



#### SPECIFICATIONS

Input Voltage	100 - 240VAC
Output Current	6A
Cooling	Convection Cooled
Output DC Voltage	28.9V Max.
Plug	Cannon/XLR
Operating Temperature	0°C - 40°C
Operating Humidity	20% - 85%RH
Dimensions	190 (L) x 145 (W) x 70mm (H)
Weight	0.0406kg

#### LED INDICATION

- Yellow on: Battery charging capacity
- Green on: Fully charged
- Orange Flash: Charger self-test fail
- Orange on: Charger not connected to battery
- Orange & Yellow on: Normal charging
- Red Flash: Battery connected in wrong polarity
- Red on: Low battery voltage/Wrong Battery

#### INNOVATIVE FEATURES

- ⦿ Convection Cooling = no fan, no noise!
- ⦿ Handle on the charger ensures it's easily portable
- ⦿ Canon/XLR plug for mobility scooters and power wheelchair applications